ELECTRICAL ENGINEERING IN JAPAN
Subject Index to Volume 115, 1995

Abnormal diagnosis: **1**, 1-9
Abnormality diagnosis: **1**, 93-103
AC-DC converter: **6**, 123-138
Acceleration power: **2**, 58-66
Activating relation: **5**, 100-111
Active method: **4**, 60-70
Adaptive algorithm: **7**, 120-129
Adaptive control: **5**, 38-51
Adjustment: **1**, 51-63
Air-core CT: **4**, 42-59
Amorphous magnetic sensor: **7**, 95-107
Analysis: **2**, 135-143
Aramid paper: **6**, 41-51
Armature reaction: **6**, 112-122
Assessment index: **8**, 33-43
Attraction region: **3**, 76-84
Autoregressive model: **1**, 1-9
Avoidance control: **1**, 22-34

Bi-based ceramic superconductor: **6**, 104-111
Bifurcation theory: **6**, 8-17
Boost chopper: **6**, 123-138
Brushless: **8**, 121-138
Bulk power self-commutated converter system: **3**, 120-134
Busbar protection: **4**, 42-59

Carbon-dioxide gas separation (PSA scheme): **3**, 64-75
Catastrophe theory: **7**, 40-48
Central load-dispatching center: **7**, 29-39
Ceramic capacitor: **2**, 1-10
Circuit breaker: **4**, 82-91
CO_2 problem: **5**, 65-74
Co_9Fe: **6**, 1-7
Colored and timed Petri nets: **2**, 89-101
Combinatorial optimization: **3**, 30-38; **6**, 71-81
Combinatorial optimization problem: **3**, 76-84
Combined supply of heat and electric power: **8**, 68-81
Commutatorless motor: **1**, 123-139
Complete blackout: **1**, 35-50; **3**, 15-29
Complex-valued load-flow calculation: **1**, 22-34
Computer graphics: **8**, 109-120
Conflict resolution: **5**, 100-111
Constant flux mode: **2**, 135-143
Continuous-type phase regulator: **3**, 50-63
Control system instability: **6**, 8-17
Convergence speed: **3**, 76-84
Cooperative control: **2**, 78-88
Coprime factorization description: **5**, 112-127
CT saturation: **5**, 10-21
Cu: **6**, 1-7
Current differential scheme: **5**, 10-21
Current limiter: **4**, 82-91
Current sense: **8**, 95-108
Current sensor: **1**, 114-122
Current-source inverter: **3**, 135-145
CV cable: **7**, 1-10

Database: **5**, 22-37
DC superimposition: **6**, 92-103
Dead zone: **4**, 60-70
Decentralized control: **8**, 44-56
Demand-and-supply control: **7**, 29-39
Dependability: **3**, 85-95
Design of superconducting machine: **1**, 123-139
Deterioration: **8**, 1-11
Dielectric breakdown of solid: **2**, 21-31
Digital control: **7**, 130-138
Digital portable telephone: **5**, 112-127
Digital processing: **4**, 92-100
Direct heat exchanger: **6**, 33-40
Direct lightning stroke: **4**, 27-41
Discrete Fourier expansion: **4**, 92-100
Discrete-time systems: **8**, 82-94
Discrimination analysis: **1**, 10-21
Dispatch control: **3**, 15-29
Dispersed generating sources: **8**, 68-81
Doubly coprime factorization: **8**, 82-94
Duffing's equation: **7**, 40-48
Dynamic characteristics: **1**, 51-63
Dynamic control: **7**, 29-39
Dynamic load model: **6**, 82-91
Dynamic model: **1**, 104-113
Dynamic voltage stability: **2**, 46-57

Economic load dispatching: **7**, 29-39; **8**, 68-81
EHV power system: **1**, 35-50; **3**, 15-29
Eigenvalue analysis: **8**, 57-67
Eigenvalue method: **4**, 14-26
Electric resistance among strands: **7**, 108-119
Electrical load forecasting: **8**, 22-32
Electrical load form factor: **3**, 39-49
Electromagnetic induction: **2**, 135-143
Electromagnetic induction method: **4**, 123-133
Emergency control: **8**, 33-43
EMI: **4**, 101-109

Energy function method: **4**, 14-26
Energy model: **5**, 65-74
Energy transfer circuit: **7**, 82-94
Error in explanatory variables: **8**, 22-32
Expert system: **1**, 35-50; **2**, 89-101; **3**, 15-29

FACTS: **2**, 58-66
Fail-safe: **2**, 115-122
Failure analysis: **2**, 115-122
Fast approximation solution method: **6**, 18-32
Fault current limiter: **6**, 104-111
Fault detection: **4**, 71-81
Fault-location scheme: **5**, 10-21
Fault-point locating: **5**, 75-87
Fault restoration: **2**, 67-77
Fault section estimation: **1**, 10-21; **2**, 89-101
Fault-section isolation: **5**, 75-87
Final prediction errors: **8**, 22-32
Flashover test: **4**, 27-41
Fluffless paper: **6**, 41-51
Flux estimation: **1**, 75-84
Flux-feedback type: **2**, 123-134
Flux observer: **2**, 123-134
Flyback converter: **5**, 128-139
Formal linearization: **4**, 92-100
Frequency of bus voltage: **2**, 32-45
Frequency shift: **4**, 60-70
Fuel cell: **3**, 64-75
Fuse: **4**, 82-91
Fuzzy control: **2**, 78-88; **5**, 52-64

Galloping: **7**, 11-28
Gas analysis: **8**, 1-11
Gas sensor: **1**, 93-103
Generation expansion planning: **6**, 71-81
Generation planning: **3**, 1-14
Generator control: **5**, 38-51, 52-64
Generator winding: **2**, 102-114
Genetic algorithms: **1**, 104-113; **3**, 30-38; **5**, 88-99
6, 18-32
Giant magnetoresistance effect: **6**, 1-7
GIS: **1**, 1-9, 64-74
Gradient method: **3**, 76-84
Grey dynamic model: **2**, 11-20
Ground coil: **4**, 134-145
Ground-fault sensor: **5**, 75-87

H_{00} control: **4**, 110-122
Hall IC: **1**, 114-122
Harmonic power detection: **3**, 96-107
Harmonic power flow: **3**, 96-107
Harmonics: **3**, 96-107
Heat treatment: **4**, 1-13
High-speed forced grounding multipole autoreclosing:
4, 42-59
High-speed phase shifter: **3**, 50-63; **8**, 44-56, 57-67
High-temperature cable: **8**, 12-21
High-voltage distribution line: **4**, 27-41
High-voltage pulse: **2**, 1-10
Hopfield network: **3**, 76-84
HSPS: **3**, 50-63
Hybridization: **6**, 18-32
Hydrogen generator: **3**, 39-49
Hydrogen storage tank capacity: **3**, 39-49

Inconnected power systems: **7**, 49-68
Indirect internal reforming scheme: **3**, 64-75
Induced lightning stroke: **4**, 27-41
Induction motor: **7**, 130-138
Inductive repulsion scheme: **4**, 134-145
Inductor converter-bridge: **7**, 82-94
Inertia moment identification: **7**, 120-129
Instantaneous speed observer: **7**, 120-129
Insulating oil: **8**, 1-11
Insulating paper: **8**, 1-11
Insulation breakdown: **7**, 1-10
Insulation design of *V-t* curve: **2**, 21-31
Insulator: **2**, 21-31
Integral controller: **8**, 82-94
Integral-type controller: **4**, 110-122
Interface insulation: **7**, 1-10
Interlock: **2**, 115-122
Interturn insulation: **6**, 41-51
Interval prediction: **2**, 11-20
IPM: **8**, 95-108
Islanding detection function: **4**, 60-70

Joints: **7**, 1-10

Large-scale interconnected systems: **8**, 44-56
Learning: **1**, 75-84
Levitation-type railway: **4**, 134-145
Lightning arrester: **4**, 27-41
Lightning impulse breakdown: **6**, 41-51
Lightning protection design: **4**, 27-41
Linear DC motor: **1**, 85-92
Linear synchronous motor: **4**, 134-145
Linguistic approximation: **3**, 1-14
Linguistic risk assessment: **3**, 1-14
Live-wire diagnosing: **6**, 92-103
Load change compensation: **8**, 57-67
Load restoration: **3**, 30-38
Long term: **1**, 51-63
Long-term load forecasting: **2**, 11-20
Loop power system control: **3**, 50-63
Loop transfer recovery: **8**, 82-94
Low-frequency oscillation: **7**, 49-68
Low-level radioactive solid waste: **5**, 1-9
Lyapunov function: **8**, 44-56

Magnetic anisotropy: **6**, 1-7
Magnetic bearing: **7**, 130-138
Magnetic levitation: **2**, 135-143; **4**, 110-122; **7**, 130-138
Magnetic sensor: **4**, 123-133
Magnetic shielding: **6**, 104-111
Magnetization processes: **6**, 1-7
Majority logic operation: **2**, 115-122
Mean time between failures (MTBF): **3**, 85-95
Measurement: **1**, 64-74
Melting: **5**, 1-9
Midterm stability: **4**, 14-26
Miniature power system model: **2**, 32-45
Mixed gas: **1**, 93-103
Mixed integer programming: **2**, 67-77
Model structure criterion: **8**, 22-32
Molten carbonate fuel cell: **3**, 64-75
Multiobjective optimization: **7**, 29-39
Multiple connection: **3**, 120-134
Multistrand superconducting conductor: **7**, 108-119
Multiterminal transmission line: **5**, 10-21
Multivariable control: **5**, 38-51

Nb_3Sn: **4**, 1-13
Network analysis: **5**, 22-37
Neural network: **1**, 10-21, 75-84, 93-103; **5**, 38-51, 88-99, **8**, 33-43
Neural vector control: **1**, 75-84
Neurocomputing: **6**, 18-32
Noise analysis: **5**, 88-99
Nonlinear capacitance: **2**, 1-10
Nonlinear control: **2**, 58-66; **5**, 38-51
Nonlinear filter: **4**, 92-100
Nonlinear observer: **4**, 92-100
Nonlinear optimization: **1**, 22-34
Nonlinear system: **4**, 92-100
Nonlinear transmission line: **2**, 1-10
Nonlinearity: **4**, 110-122; **7**, 40-48
Null flux: **4**, 134-145
Numerical integration: **1**, 51-63
Numerical simulation: **3**, 76-84

Ocean energy technology: **6**, 33-40
On-line diagnosis: **5**, 88-99
One-machine intermediate-load power system model: **7**, 49-68
Open cycle ocean thermal conversion system: **6**, 33-40
Optimal generation introduction: **6**, 71-81
Optimal introduction planning: **8**, 68-81
Optimization: **5**, 65-74
Overvoltage protection: **4**, 42-59

$\Delta\omega$ (Δf) + ΔP-type PSS: **7**, 49-68

Parallel genetic algorithm: **6**, 71-81
Parallel operation: **8**, 95-108
Parallel processing: **2**, 89-101
Parallel processors: **6**, 71-81
Parallel redundant operation: **3**, 85-95
Parallel resonant circuit: **3**, 135-145
Parallel running: **6**, 62-70
Parameter tuning: **1**, 104-113
Partial current distribution: **7**, 108-119
Partial discharge: **1**, 1-9; **8**, 1-11
Perfluorocarbon liquid: **6**, 41-51
Persistent current: **2**, 135-143
Petri net: **2**, 89-101; , 100-111
Photovoltaic/fuel cell power hybrid system: **3**, 39-49
Photovoltaic power generation: **3**, 135-145
Photovoltaic system: **5**, 128-139
Piezoelectric element: **7**, 69-81
Place invariant: **5**, 100-111
Planar transformer: **2**, 115-122
Plane ultrasonic actuator: **7**, 69-81
Plasma heating: **5**, 1-9
Point prediction: **2**, 11-20
Polyimide insulation: **8**, 12-21
Polyphase reclosing scheme: **2**, 46-57
Power capacitors: **8**, 1-11
Power distribution automation: **5**, 75-87
Power distribution line protection: **5**, 75-87
Power factor: **6**, 123-138
Power plant: **1**, 104-113
Power supply for superconducting magnet: **7**, 82-94
Power system: **1**, 22-34; **2**, 67-77, 78-88; **4**, 14-26; **5**, 128-139; **7**, 29-39, 40-48; **8**, 68-81
Power system engineering: **3**, 1-14
Power system protection: **5**, 22-37
Power system stabilization: **8**, 57-67
Power system stabilizer: **2**, 58-66
Power system voltage stability: **6**, 82-91
P_q theory: **3**, 96-107
Prefabricated-type joints: **7**, 1-10
Preventive control: **1**, 22-34; **4**, 14-26
Projectile: **1**, 85-92
Protective relay: **5**, 22-37
Pulse width modulation (PWM): **3**, 135-145
PWM: **3**, 120-134
PWM power inverter: **5**, 128-139

Radiation-resistant cable covering: **8**, 12-21
Railgun: **1**, 85-92
Reactor: **5**, 88-99
Reactor-current boundary conduction mode: **6**, 123-138
Reactor-current discontinuous conduction mode: **6**, 123-138
Relay setting: **5**, 22-37

Restoration operation: **1**, 35-50
Restorative operation: **3**, 15-29
Robust: **2**, 123-134
Robust control: **2**, 58-66

Search of buried object: **4**, 123-133
Search of harmonic source: **3**, 96-107
Second-space harmonic component: **6**, 112-122
Secondary-current sensor: **7**, 95-107
Secondary resistance variation: **2**, 123-134
Secondary-resistance temperature compensation: **7**, 95-107
Section location: **4**, 71-81
Self-excitation scheme: **6**, 112-122
Self-organization: **8**, 22-32
Self-restoring-type current limiting device: **4**, 82-91
Sensor: **1**, 64-74
Separately excited scheme: **8**, 121-138
Sequential control system: **5**, 100-111
Setting-value change: **5**, 52-64
Signal processing: **1**, 1-9
Silicon oil: **7**, 1-10
Simulating calculation: **7**, 11-28
Simulation: **1**, 104-113; **5**, 22-37; **6**, 82-91; **8**, 57-67, 109-120
Single-phase converter: **3**, 120-134
Single-phase inverter: **3**, 135-145
Slider: **7**, 69-81
Sliding mode: **2**, 58-66, 78-88
Slip-frequency type: **2**, 123-134
SMES: **8**, 57-67
Sodium current limiter: **4**, 82-91
Solar cell: **5**, 128-139
Sputtering: **4**, 1-13
Stability: **7**, 108-119
State stability limit: **6**, 62-70
Static var compensator: **6**, 8-17
Stator: **7**, 69-81
Steady-state stability: **8**, 44-56
Steady-state torque control: **7**, 95-107
Steep impulse voltage: **2**, 21-31
Step size: **1**, 51-63
Substation: **8**, 109-120
Superconducting generator: **2**, 102-114; **6**, 62-70
Superconducting magnetic energy storage system (SMES): **2**, 32-45
Superconducting motor: **1**, 123-139
Superconductivity: **1**, 123-139; **2**, 135-143
Superconductor wires: **4**, 1-13
Swing control: **2**, 78-88
Switching frequency: **3**, 120-134
Switching loss: **4**, 101-109
Switching regulator: **5**, 112-127
Synchronous motor: **7**, 130-138
System interconnection: **3**, 135-145
System interconnection protection equipment: **4**, 60-70
1000-kV system protection: **4**, 42-59
System unbalance: **2**, 46-57

Target: **4**, 1-13
Technology evaluation: **5**, 65-74
Theory of oscillation occurrence: **7**, 11-28
Thin film sandwiches: **6**, 1-7
Three-phase composition: **4**, 71-81
Three-phase converter: **3**, 120-134
Three-phase current: **1**, 114-122
Three-phase synchronous generator: **6**, 112-122
Three-phase synchronous induction motor: **8**, 121-138
Three-phase-short fault: **6**, 62-70
Topological forecasting: **2**, 11-20
Transformer: **1**, 93-103
Transformer insulation: **6**, 41-51
Transformer protection: **4**, 42-59
Transient electromagnetic force: **2**, 102-114
Transient magnetic field: **2**, 102-114
Transient stability: **4**, 14-26; **5**, 38-51
Transmission expansion planning problem: **6**, 18-32
Transmission line: **7**, 11-28
Two poles on imaginary axis: **4**, 110-122
Two stators: **8**, 121-138
Two-degree-of-freedom controllers: **8**, 82-94
Two-degrees-of-freedom control system: **5**, 112-127

Ultralow-speed operation: **7**, 120-129
Uncertain factors: **3**, 1-14
Underground line: **4**, 123-133
Ungrounded power transmission line: **4**, 71-81
Uninterruptible power supply (UPS): **3**, 85-95
Uninterruptible transfer switch: **3**, 85-95
Unstable phenomenon: **7**, 40-48

Variable series capacitor: **8**, 44-56
Variable-impedance apparatus: **2**, 58-66
Vector control: **2**, 123-134
VFTO: **1**, 64-74
Virtual reality: **8**, 109-120
Voltage collapse: **6**, 82-91
Voltage control: **1**, 35-50
Voltage divider: **1**, 64-74
Voltage instability phenomena: **2**, 46-57
Voltage stability: **1**, 22-34; **8**, 33-43
Voltage stability limit: **6**, 82-91
Volume reduction: **5**, 1-9

Weaving-loom shuttle: **1**, 85-92

X-ray diffraction: **4**, 1-13
XLPE cable: **6**, 92-103

YJB parametrization: **8**, 82-94

Zero-current-switching pulse width modulation inverter : **4**, 101-109
Zero method: **1**, 114-122
Zero-phase current: **1**, 114-122
Zero-phase-sequence current: **4**, 71-81